



 **FIELDMASTER DISC**



**Thyregod
Fieldmaster**

Fieldmaster Disc



The Fieldmaster Disc ensures an effective injection of slurry, also on soils with a lot of plant material left on the ground.



Golf clubs & double depth wheels

As an lighter alternative to the flat bar roller, the Fieldmaster can be equipped with golf clubs and double depth wheels.



| Technical data | Fieldmaster Disc | |
|--|-----------------------------|-----------|
| Working width | 6.0 meter | 8.0 meter |
| Transport height | 3.5 meter | 4.0 meter |
| Transport width | 3.0 meter | |
| Discs | 46 pcs | 62 pcs |
| Disc spacing | 27 cm - Cross mounted L / R | |
| Working depth | 2 - 12 cm | |
| Harrow type | Flat-bar-roller ø600 mm | |
| Distributor | Hydraulic with 4 arms rotor | |
| Depth adjustment | Steeple hydraulic | |
| Injection volume | 8 - 50 m ³ / ha | |
| Slurry trailer | All models | |
| Pulling eyes rear | 2 pcs standard | |
| Options | | |
| ø620mm Discs | | |
| Vertical Distributer, with stonetrap | | |
| Golf clubs, instead of roller | | |
| Double depth wheels, hydraulic adjustable | | |
| Small tined double harrow, instead of roller | | |



Spring mounted discs

The discs are cross mounted right / left, ensuring that the Fieldmaster does not pull to one side.

Large distance between the disc rows helps to ensure continuous operation even with much plant material left in the field.



Always correct working depth

The Fieldmaster work individually in 3 sections and is fitted with 3 ø300mm rollers.

The rollers are suspended and are individually hydraulic adjustable.

Rollers and depth wheels (if fitted) are easily adjusted at the rear.

