



**FIELDMASTER**

# Thyregod Fieldmaster



The Fieldmaster Disc ensures an effective injection of slurry, also on soils with a lot of plant material left on the ground.



Golf clubs & double depth wheels  
As an lighter alternative to the flat bar roller, the Fieldmaster can be equipped with golf clubs and double depth wheels.



Tecnical data	Fieldmaster 6000 / 8000	
Working width	6.0 meter	8.0 meter
Transport height	3.5 meter	4.0 meter
Transport width	3.0 meter	
Injectors	23 pcs	31 pcs
Injector distance	26 cm	
Working depth	2 - 15 cm	
Harrow type	Flat-bar-roller ø600 mm	
Distributor	Hydraulic with 4 arms rotor	
Depth adjustment	Steeples hydraulic	
Injection volume	8 - 50 m <sup>3</sup> / ha	
Slurry trailer	All models	
Anbefalet trækraft	Ca. 60 - 80 hk	
Pulling eyes rear	Standard	

## Options

Vertical Distributer, with stonetrap  
Golf clubs, instead of roller  
Double depth wheels, hydraulic adjustable  
Small tined double harrow, instead of roller



Best way to working in the field!

Fieldmaster Black soil injector are build in 6 or 8 meters working width.

The large height of the frame and the large distance between the injectors helps to ensure continuous operation even with much



Always correct working depth

The Fieldmaster work individually in 3 sections and is fitted with 3 ø600mm rollers.

The rollers are suspended and are individually hydraulic adjustable.

Rollers and depth wheels(*if fitted*) are easily adjusted at the rear.



Thyregod A/S - Borgergade 46 - DK-7323 Give - Tlf. 7573 4099  
thyregod@thyregod.com - www.thyregod.com