



# SLURRY PUMPS



**Stationary slurry pumps**

**Bottom inlet**



# SLURRY PUMPS

KIMADAN's production of stationary long-shaft slurry pumps today offers countless variations of pumps for forechambers and storage tanks.

Because of their high performance and good emptying characteristics, the main application of bottom inlet pumps (which are in fact the original standard KIMADAN pumps) is in connection with slurry storage tanks.

KIMADAN Bottom inlet pumps are available as 5" electrical pumps with 10, 15, 20 and 25 hp motor, and 5" and 6" PTO pumps for tractor operation.



All KIMADAN pumps are galvanised and flanged together. Pump housings are impact-resistant castings which mean robustness and long operating life. Further features which also add to long-term pump reliability and minimum wear are the steel, slurry-lubricated bearings and the low pump speed. KIMADAN pumps are made to dimensions suitable for YOUR slurry tanks precisely.

See also the product sheet for KIMADAN Top inlet pumps.



## SPECIFICATION

Power requirement:	Electric motor 10-25 hp PTO 35-45 hp
Weight:	280-400 kg
Pump size:	5"-6"
Pump capacity:	2500-7000 l/min
Working ranges:	1.5-5.5 m tank depth



### Thyregod A/S

Borgergade 46

Thyregod

DK-7323 Give

Telefon +45 7573 4099

Fax. +45 7573 4492

E-mail:

[thyregod@thyregod.com](mailto:thyregod@thyregod.com)

[www.thyregod.com](http://www.thyregod.com)