



SLURRY PUMPS



Stationary slurry pumps
Top inlet



SLURRY PUMPS

KIMADAN's production of stationary long-shaft slurry pumps today offers countless variations of pumps for forechambers and storage tanks.

KIMADAN Top inlet pumps are made especially for heavy duty in forechambers. Here the emphasis is on a pump with high delivery pressure, able to cope with the large distance to storage tanks and the long flush-out lines. The top inlet in the pump housing and the feed screw enable the pump to handle heavy slurry containing a large quantity of cut straw.



KIMADAN Top inlet pumps are available as 5" electrical pumps with 15, 20 and 25 hp motor, and 6" PTO pumps for tractor operation or as electrical pumps with a 40 hp motor.

All KIMADAN pumps are galvanised and flanged together. They are fitted with steel, slurry-lubricated bearings.

KIMADAN pumps are made to dimensions suitable for YOUR slurry tanks precisely.

See also the product sheet for KIMADAN Bottom inlet pumps.



SPECIFICATION

Power requirement:	Electric motor 15-25-40 hp PTO 60-100 hp
Weight:	280-550 kg
Pump size:	5"-6"
Pump capacity:	3500-7000 l/min
Working ranges:	1.5-5.5 m tank depth



Thyregod A/S

Borgergade 46
Thyregod
DK-7323 Give
Telefon +45 7573 4099
Fax. +45 7573 4492
E-mail:
thyregod@thyregod.com
www.thyregod.com