



DRAIN AND SLURRY PUMP



**TYPE: 700 M 700 M-A
750 M**

Drain and slurry pump

The pump can be supplied in length from 0,75 m and up to 5,0 m.

With good results the pump is very effective at slaughter-fish and oil factory; it can also be used on ships.

The pump is also made at special requests' so please ask.



700 M

Engine: 1,5 HP – 1,1 kW 3 x 380 volt 1400 rpm.
Capacity: 550 liter per minute at 2,5 m. lifting height
Maximum lifting height 7,50 m.
Dimensions: Length 2,50 m. 2" galv. pipe

700 M-A

Engine: 4 HP – 3,0 kW 3 x 380 volt 2800 Rpm.
Capacity: 700 liter per minute at 2,5 m. lifting height
Maximum lifting height 15 m.
Dimensions: Length 2,50 m. 2" galv. pipe

750 M

Engine: 4 Hp – 3,0 kW 3 x 380 volt, 1400 rpm.
Capacity: 1100 liter per minute at 2,50 m. lifting height
Maximum lifting height 8,0 m.
Dimensions: Length 3,00 m. 3" galv. pipe



Thyregod A/S

Borgergade 46

Thyregod

DK-7323 Give

Telefon +45 7573 4099

Fax. +45 7573 4492

E-mail:

thyregod@thyregod.com

www.thyregod.com